



WINE		mm LxPxI	0,75 LT	LIGHT	LT	Kg	kW	V	
	PVW-1-R6	860x530x938	48	○○○	216	66	0,4	230/1N 50Hz	5 618,00 EUR
	PVW-1/TR-R6	860x530x938	48	○○○	216	73	0,4	230/1N 50Hz	5 852,00 EUR
	R600A								
	 +8 °C +4 °C Set 4 °C ON TA 25 °C	 +16 °C +14 °C Set 14 °C ON TA 30 °C	 +16 °C +10 °C +4 °C Set 4 °C OFF TA 25 °C	 MRX mm ø 90 mm h 370 mm					

WINE		mm LxPxI	0,75 LT	LIGHT	LT	Kg	kW	V	
	PVW-2-R6	860x530x938	42	○○○	216	66	0,4	230/1N 50Hz	5 911,00 EUR
	PVW-2/TR-R6	860x530x938	42	○○○	216	73	0,4	230/1N 50Hz	6 145,00 EUR
	R600A								
	 +8 °C +4 °C Set 4 °C ON TA 25 °C	 +16 °C +14 °C Set 14 °C ON TA 30 °C	 +16 °C +10 °C +4 °C Set 4 °C OFF TA 25 °C	 MRX mm ø 120 mm h 400 mm					

WINE		mm LxPxI	0,75 LT	LIGHT	LT	Kg	kW	V	
	PVW-3-R6	860x530x938	64	○○○	216	70	0,4	230/1N 50Hz	5 618,00 EUR
	PVW-3/TR-R6	860x530x938	64	○○○	216	77	0,4	230/1N 50Hz	5 852,00 EUR
	R600A								
	 +8 °C +4 °C Set 4 °C ON TA 25 °C	 +16 °C +14 °C Set 14 °C ON TA 30 °C	 +16 °C +4 °C Set 4 °C OFF TA 25 °C						

WINE		mm LxPxI	0,75 LT	LIGHT	LT	Kg	kW	V		
	PVW-4-R6	860x530x938	42/64	○○○	216	62	0,4	230/1N 50Hz	5 443,00 EUR	
	PVW-4/TR-R6	860x530x938	42/64	○○○	216	69	0,4	230/1N 50Hz	5 677,00 EUR	
	R600A									
	 +10 °C +4 °C Set 4 °C ON	 +16 °C +14 °C Set 14 °C ON	 +16 °C +10 °C +4 °C Set 4 °C OFF	OPTIONAL						
	 OP4-A 4	 OP4-B3 8	 OP4-C 7	 OP4-D 16						