



To maintain the performance of the cooling units and to ensure a long service life of the units regular maintenance is required. For detailed information please refer to the operating instructions:



- The device must always be disconnected from the power supply during maintenance.
- The condenser should be cleaned every three months with a vacuum cleaner or brush from top to bottom (Attention, the lamellas are sharp!), in order to avoid the claim of the manufacturer's guarantee.
- Existing filters should be dedusted or removed at regular intervals be degreased. The best way to do this is to use water with a fat-dissolving Detergent and a brush. The filters can after drying be reinstated.
- Check the seals on your device regularly. Remove dirt or grease or replace the brittle seal.
- Clean the interior and the drain, to ensure the drainage of condense water.
- Cooling maintenance may only be carried out by qualified personnel.



GN 650 TN PRO

Commercial refrigerator MODELL GN 650 TN PRO

- Complete structure inside & outside in stainless steel AISI 304 with rounded inner edges
- for easy cleaning
- Insulation 100 mm thick for better energy efficiency
- Automatic defrosting and automatic evaporation of condensed water
- Electronic thermostat and digital LED temperature display for accurate control and easy reading (DIXELL)
- Self-closing door
- Magnetic seal can be replaced without tools
- Refrigerant: R600a
- Energy efficiency class: B (range A+++ to E)



Model	Order no.	GTIN	Price
GN 650 TN PRO	323-10205	4017337057702	3.048,00 €
230 V - 50 Hz - 0,55 kW	-2 / +8	86	
Int.: W 533 mm x D 700 mm x H 1397 mm Ext.: W 740 mm x D 830 mm x H 2010 mm	GN 2/1	521	

