

Icecrusher Model EC 80

- Material: stainless steel / plastic
- 800 rpm
- Noise level: <85 dB when in use
- Container capacity: 3.1 L
- Anti-slip feet



Model	Order no.	GTIN	Price
EC 80	418-3000	4017337056903	438,00 €
230 V - 50 Hz - 0,2 kW	5,4/7,1		
W 390 x D 275 x H 580 mm			

Flake ice machine Model F 90 C A/W, F 120 C A/W, F 160 C A/W

- Material: (housing) stainless steel, (container door) plastic
- Air cooling (A) or water cooling (W)
- Production capacity of flake ice in 24 hours: 94 kg (F 90 C), 120 kg (F 120 C), 160 kg (F 160 C)
- Container capacity: 18 kg (F 90 C / F 120 C) and 50 kg (F 160 C)
- Collecting container with infrared level sensor
- Only model F 160 C with adjustable feet, can be ordered as an option for models F 90 C and F 120 C
- Suitable for ambient temperatures from 10 °C to 40 °C, for water temperatures from 10 °C to 35 °C with a water pressure of 1 - 5 bar
- A water softener is recommended if the water hardness is greater than 7 °
- Including hose for 3/4 inch fixed water connection and drain hose 0 20 mm
- Refrigerant: R134a (GWP 1430)
- F 90 C A / W: 250 g; 0.358 t CO2 equivalent
- F 120 C A / W: 270 g; 0.386 t CO2 equivalent
- F 160 C A: 380 g; 0.543 t CO2 equivalent
- F 160 C W: 400 g; 0.572 t CO2 equivalent



F 90 C

Model	Order no.	GTIN	Price
F 90 C A	463-1100	4017337063277	4.508,00 €
F 90 C W	463-1105	4017337063284	4.508,00 €
F 120 C A	463-1110	4017337063376	4.838,00 €
F 120 C W	463-1115	4017337063383	4.829,00 €
F 160 C A	463-1200	4017337059188	5.169,00 €
F 160 C W	463-1205	4017337059195	5.214,00 €

	F 90 C A/W	F 120 C A	F 120 C W	F 160 C A	F 160 C W
230 V - 50 Hz -	0,703 kW	0,490 kW	0,90 kW	0,650 kW	0,530 kW
kg	55	57	57	84	84
	W 500 x D 606 x H 694 mm (optional with feet H 775/1016 mm)			W 700 x D 616 x H 995/1016 mm	

